

TimberIN sauna trailer – technical sheet

Every TimberIN mobile sauna can be ordered on its own road trailer, built for transporting a sauna.

The trailer length is matched to the selected sauna length.

Technical data

Type	Twin-axle centre-axle platform trailer with floor, braked, for transporting a sauna
EU vehicle category	O2
Gross vehicle weight	2,000 kg (standard) or 2,700 kg version
Permissible axle loads	2 × 1,000 kg (2,000 kg version) · 2 × 1,350 kg (2,700 kg version)
Axles	2 axles, 1,350 kg each
Unladen weight	approx. 450 kg
Tyres	4 × 185R14C 104N M+S
Rims	5.5J × 14 H2, ET30, 5 × 112
Wheel position	Outside the platform
Coupling	Overrun coupling; coupling height 430 mm above the road (fixed)
Max. vertical load on the coupling	100 kg
Lighting	12 V, 13-pin plug
Jockey wheel	60 mm / 150 kg
Corner support legs	4
Wheel chocks	2
Platform width	1.5 m or 2.0 m; 2.07 m optional
Platform length	Matched to the selected sauna length
Example: 5.0 × 2.0 m platform	Overall length 6,501 mm incl. drawbar; platform width 2,000 mm
Example: 4.0 m loading length	Overall length 5,520 mm; overall width 1,960 mm; height 760 mm (unladen)
Type approval and documents	EU type-approved (Directive 2007/46/EC). Supplied with a Certificate of Conformity (CoC) and an identity-data certificate for registration; it can be permanently registered in EU member states.

Delivery and unloading

When ordered with the trailer, the sauna is delivered already mounted on it. Because of the truck's height limit, the trailer wheels are removed for transport. Lifting equipment, either a crane or a forklift, must be available on site to lift the sauna off the truck, refit the wheels and set the trailer down on the ground.